

Printing	PJ-622	PJ-662	PJ-623	PJ-663	PJ-673
Print resolution	203 x 200 dpi		300 x 300 dpi		
Print technology	Direct thermal				
Printing speed	Ave.: 9.4 sec./page or 31.6 mm/second (under Brother standard environment *1)				
Paper feed method	Manual paper feed				
Printable area	203.2 x 279.4 (maximum)				
No. of pages per battery charge	Rechargeable Li-ion Battery: approximately 300 Sheets / Rechargeable Ni-MH Battery: approximately 70 Sheets (1.9% printing duty and using a fully charged new battery)				
Interface					
USB	USB Ver.2.0 (full speed) type A to mini type B (printer)				
IrDA	Ver.1.2 (IrCOMM and IrOBEX)				N/A
Bluetooth	N/A	Ver. 2.0+EDR Class 2 SPP & BIP Profiles Supported	N/A	Ver. 2.0+EDR Class 2 SPP & BIP Profiles Supported	N/A
Wireless-LAN	N/A	N/A	N/A	N/A	IEEE 802.11b/g (Adhoc mode) Open System / WEP (64/128 bit)
PJ ESC/P language					
Built-in Fonts	Serif and Sans Serif				
Font Sizes	10 cpi, 12 cpi, 15 cpi and Proportional Sizes				
Barcode support	No				
Template/Form Storage					
Memory Size	N/A	N/A	5,888KB	5,888KB	N/A
Memory Locations	N/A	N/A	99	99	N/A
General					
Dimensions	255(W) x 55(D) x 30(H) mm 10.04 x 2.17 x 1.18 in.				255(W) x 55(D) x 40(H) mm 10.04 x 2.17 x 1.6 in.
Weight	Approximately 470g (excluding battery & paper)	Approximately 473g (excluding battery & paper)	Approximately 470g (excluding battery & paper)	Approximately 473g (excluding battery & paper)	Approximately 478g (excluding battery & paper)
Battery	Rechargeable Ni-MH Battery 14.4V / Rechargeable Li-ion Battery 11.1V (Optional Accessories)				
AC adapter	AC adapter 15 V (Optional Accessory)				
Car adapter	2 types: Cigar Lighter Plug or Permanently Wired (Optional Accessories)				
Operating systems support	Windows XP / Vista / 7 / 8 (USB) Mac OS X	Windows XP / Vista / 7 / 8 (USB/Bluetooth) Mac OS X	Windows XP / Vista / 7 / 8 (USB) Mac OS X	Windows XP / Vista / 7 / 8 (USB/Bluetooth) Mac OS X	Windows XP/Vista / 7/8 (USB) Apple iOS 4.3 or later
Environmental					
Temperature	0°C to +40°C (During Operation) / -15°C to +50°C (During Storage)				
Humidity	30% to 80% (No Condensation - During Operation) / 30% to 85% (No Condensation During Storage)				
Auto Power Off	Yes: 7 Settings (0, 10, 20, 30, 40, 50, 60 minutes)				
Contents					
Items included	PocketJet Printer (PJ-622 / PJ-623 / PJ-662 / PJ-663 / PJ-673) Quick Setup Guide CD-ROM (Printer Driver and User's Manual) USB cable Head Cleaning Sheet				