	QL-560	QL-570	QL-580N	QL-1050	QL-1060N
Power Requirements	Internal power supply - 220-240V AC	Internal power supply - 220-240V AC	Internal power supply - 220-240V AC	Internal power supply - 220-240V AC	Internal power supply - 220-240V AC
Printer Dimensions	146mm(W) x 196mm(D) x 152mm(H)	134mm(W) x 208mm(D) x 141mm(H)	134mm(W) x 240mm(D) x 141mm(H)	171mm(W) x 224mm(D) x 148mm(H)	171mm(W) x 224mm(D) x 148mm(H)
Print Head	Direct thermal - 300x300 dpi	Direct thermal - 300x600 dpi	Direct thermal - 300x600 dpi	Direct thermal - 300x300 dpi	Direct thermal - 300x300 dpi
Maximum Print Speed*	90mm/second - 56 labels/minute	110mm/second - 68 labels/minute	110mm/second - 68 labels/minute	110mm/second - 69 labels/minute	110mm/second - 69 labels/minute
Maximum Label Width	62 mm	62 mm	62 mm	102 mm	102 mm
Maximum Print Height	59 mm	59 mm	59 mm	98.6 mm	98.6 mmMaximum Print Height
Maximum Label Length	1 metre	1 metre	1 metre	3 metre	3 metre
Automatic Cutter	Built-in user replaceable cutter	Built-in permanent cutter	Built-in permanent cutter	Built-in permanent cutter	Built-in permanent cutter
Interface(s)	USB 1.1 or later specification	USB 1.1 or later specification	USB 1.1 or later specification RS-232 9-pin D-Sub Network (10/100 Base-TX wired ethernet)	USB 1.1 or later specification RS-232 9-pin D-Sub	USB 1.1 or later specification RS-232 9-pin D-Sub Network (10/100 Base-TX wired ethernet)
	System Requirements PC		System Requirements Mac		

	System Requirements PC	System Requirements Mac		
Operating System**	Microsoft Windows® 2000 Professional / Windows XP® / Windows Vista®	Operating System Support**	Mac OS X 10.3.9 to 10.5.1	
Minimum CPU Speed	As recommended by operating system specifications	CPU	PowerPC or Intel	
Minimum Memory (RAM)	As recommended by operating system specifications	Minimum Memory (RAM)	As recommended by operating system specifications	
Hard Disk Free Space	70MB or more	Hard Disk Free Space	100MB or more	
Interface(s)	As per individual model specifications (above)	Interface(s)	As per individual model specifications (above) - excluding RS-232	
Graphics Card	SVGA with minimum 16 bit colour depth	Graphics Card	More than 256 colours	
Other	CD-ROM drive for installation	Other	CD-ROM drive for installation	

^{*} Based on standard address labels ** For latest operating system support information visit http://solutions.brother.com



